


| Specifications | | SLH2-18 | SLH2-36 | SLH2-68 | SLH2-130 |
|---|--|---|---------------|---------------|---------------|
| Maximum continuous voltage (DC) | U_c | 16 V | 34 V | 65 V | 155 V |
| Maximum continuous voltage (AC) | U_c | 11 V | 24 V | 46 V | 130 V |
| Maximum discharge current (8/20 μ s) | I_{max} | 10 kA per line (20 kA common mode) | | | |
| Maximum impulse current (10/350 μ s) | I_{imp} | 2.5 kA per line (5 kA common mode) | | | |
| Impulse durability | | C2 8/20 μ s 10 kA - D1 10/350 μ s 5kA | | | |
| Maximum load current | I_L | 2.5 A | 2.5 A | 2.5 A | 2.5 A |
| L-L Voltage protection level @ 1 kV/ μ s | U_p | < 25 V | < 70 V | < 140 V | < 300 V |
| L-PE Voltage protection level @ 1 kV/ μ s | U_p | < 350 V | < 350 V | < 350 V | < 600 V |
| Line resistance | | 0.06 Ω | 0.06 Ω | 0.06 Ω | 0.06 Ω |
| Dimensions |  | W 12 mm x H 110 mm x D 71 mm | | | |